IN THE CLAIMS:

Please amend the claims as follows:

Claim 1 (Currently Amended): A flat type fluorescent lamp comprising:

first and second substrates;

a light-emitting layer disposed between the first and second substrates;

a plurality of supporters selectively arranged on an entire surface of the

first substrate; and

a light-scattering layer placed over the plurality of supporters, to prevent

the light scattering layer from subsiding, wherein the light-scattering layer is

spaced a distance from the first substrate, and wherein the light emitting layer is

fluorescent.

Claim 2 (Original): The flat type fluorescent lamp as claimed in claim 1, further

comprising a reflecting portion adjacent a lower portion of the second substrate.

Claim 3 (Original): The flat type fluorescent lamp as claimed in claim 1, wherein the

supporters are formed of a transparent material.

Claim 4 (Original): The flat type fluorescent lamp as claimed in claim 1, wherein the

supporters are formed of a material having characteristic for scattering light.

Application No.: 10/000,093

Page 3

Claim 5 (Original): The flat type fluorescent lamp as claimed in claim 1, wherein the

supporters are column-shaped having an upper and lower surface each with a given

surface area.

Claim 6 (Original): The flat type fluorescent lamp as claimed in claim 5, wherein the

surface area of the upper surface is different than the surface area of the lower surface.

Claim 7 (Original): The flat type fluorescent lamp as claimed in claim 5, wherein the

surface area of the upper surface is substantially equal to the surface area of the lower

surface.

Claim 8 (Original): The flat type fluorescent lamp as claimed in claim 5, wherein the

supporters are cylindrical-shaped.

Claim 9 (Original): The flat type fluorescent lamp as claimed in claim 5, wherein the

supporters are shaped like polygonal poles.

Application No.: 10/000,093

Page 4

Claim 10 (Original): The flat type fluorescent lamp as claimed in claim 1, wherein the

supporters include a lower surface having a cylindrical shape.

Claim 11 (Original): The flat type fluorescent lamp as claimed in claim 10, wherein the

supporters include an upper surface that is substantially curved.

Claim 12 (Original): The flat type fluorescent lamp as claimed in claim 11, wherein the

upper surface has a spherical shape.

Claim 13 (Original): The flat type fluorescent lamp as claimed in claim 1, wherein the

supporters include a lower surface having a polygonal shape.

Claim 14 (Original): The flat type fluorescent lamp as claimed in claim 13, wherein the

supporters include an upper surface that is substantially curved.

Claim 15 (Original): The flat type fluorescent lamp as claimed in claim 14, wherein the

upper surface has a spherical shape.

Application No.: 10/000,093

Page 5

Claim 16 (Original): The flat type fluorescent lamp as claimed in claim 1, wherein the

supporters include an upper surface that is substantially curved.

Claim 17 (Original): The flat type fluorescent lamp as claimed in claim 16, wherein the

upper surface has a spherical shape.

Claim 18 (Original): The flat type fluorescent lamp as claimed in claim 1, further

comprising a cap disposed between the supporters and the light-scattering layer.

Claim 19 (Original): The flat type fluorescent lamp as claimed in claim 18, wherein the

cap is formed by covering the supporters.

Claim 20 (Original): The flat type fluorescent lamp as claimed in claim 18, wherein the

cap is attached to the upper portion of the supporters.

Claim 21 (Original): The flat type fluorescent lamp as claimed in claim 18, wherein the

cap is formed from a soft material.

Application No.: 10/000,093

Page 6

Claim 22 (Original): The flat type fluorescent lamp as claimed in claim 1, wherein the supporters are formed separately from the first substrate.

Claim 23 (Currently Amended): A flat type luminescent lamp comprising:

a first substrate including a plurality of supporters <u>selectively arranged on an</u> entire surface of the first substrate to form a single body;

a second substrate placed opposing the first substrate;

a light-emitting layer disposed between the first and second substrates; and

a light-scattering layer placed above the plurality of supporters, to prevent the light scattering layer from subsiding, wherein the light-scattering layer is spaced a

distance from the first substrate.